



VT4883 CARDIOID VT4886 LONG THROW MIXED V4 Crown I-Tech (26 dB Gain)



NAME	PRESET	DESCRIPTION	CH 1	CH 2
MIXED 4883 / 4886 LONG THROW PRESETS				
VT4883 FRONT 80 / VT4886 LT	1	* 80 Hz crossover point: VT4883 cardioid front-firing + VT4886 (HF pre-emphasis)	VT4883 F	VT4886
VT4883 FRONT 120 / VT4886 LT	2	** 120 Hz crossover point: VT4883 cardioid front-firing + VT4886 (HF pre-emphasis)	VT4883 F	VT4886
VT4883 FRONT 160 / VT4886 LT	3	** 160 Hz crossover point: VT4883 cardioid front-firing + VT4886 (HF pre-emphasis)	VT4883 F	VT4886
VT4883 FRONT 300 / VT4886 LT	4	** 300 Hz crossover point: VT4883 cardioid front-firing + VT4886 (HF pre-emphasis)	VT4883 F	VT4886
	5	INTENTIONALLY BLANK		
VT4883 C1 REAR 80 VT4886 LT	6	* 80 Hz crossover point: VT4883 cardioid configuration 1 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C1R	VT4886
VT4883 C1 REAR 120 VT4886 LT	7	** 120 Hz crossover point: VT4883 cardioid configuration 1 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C1R	VT4886
VT4883 C1 REAR 160 VT4886 LT	8	** 160 Hz crossover point: VT4883 cardioid configuration 1 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C1R	VT4886
VT4883 C1 REAR 300 VT4886 LT	9	** 300 Hz crossover point: VT4883 cardioid configuration 1 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C1R	VT4886
	10	INTENTIONALLY BLANK		
VT4883 C2 REAR 80 VT4886 LT	11	* 80 Hz crossover point: VT4883 cardioid configuration 2 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C2R	VT4886
VT4883 C2 REAR 120 VT4886 LT	12	** 120 Hz crossover point: VT4883 cardioid configuration 2 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C2R	VT4886
VT4883 C2 REAR 160 VT4886 LT	13	** 160 Hz crossover point: VT4883 cardioid configuration 2 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C2R	VT4886
VT4883 C2 REAR 300 VT4886 LT	14	** 300 Hz crossover point: VT4883 cardioid configuration 2 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C2R	VT4886
	15	INTENTIONALLY BLANK		
VT4883 C3 REAR 80 VT4886 LT	16	* 80 Hz crossover point: VT4883 cardioid configuration 3 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C3R	VT4886
VT4883 C3 REAR 120 VT4886 LT	17	** 120 Hz crossover point: VT4883 cardioid configuration 3 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C3R	VT4886
VT4883 C3 REAR 160 VT4886 LT	18	** 160 Hz crossover point: VT4883 cardioid configuration 3 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C3R	VT4886
VT4883 C3 REAR 300 VT4886 LT	19	** 300 Hz crossover point: VT4883 cardioid configuration 3 rear-firing + VT4886 (HF pre-emphasis)	VT4883 C3R	VT4886

- NOTES
- * Physically Separate configuration (VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)
Additional time delay required to account for geometric path difference between VT4886 and VT4883
Enable optional Input PEQ1 for use in Closely Coupled configurations (VT4886 stacked on top of VT4883 or suspended below VT4883)
 - ** Closely Coupled configuration (VT4886 stacked on top of VT4883 or suspended below VT4883)
Enable optional Input PEQ1 for use in Physically Separate configurations
(VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)