

Nano KX

Bluetooth volume controller that integrates Bluetooth streaming into non-Bluetooth systems



KEY FEATURES

- Adds Bluetooth 3.0 wireless audio streaming to non-Bluetooth-capable production environments
- Easy-to-use: one volume knob and practical design provide simple control
- Illuminated level control ring for easy operation in low-light situations
- Compact footprint and stylish design keeps your workspace uncluttered
- Balanced XLR/TRS combo inputs and XLR outputs offer professional-grade connections and seamless compatibility with studio or PA equipment
- 3.5mm auxiliary input and output for more connection flexibility
- Powered via Mini-USB

The JBL Nano KX Bluetooth-enabled volume controller is perfect for content creators, home-recording enthusiasts as well as mobile DJs and performers who want to integrate Bluetooth into their project studio or non-Bluetooth, portable PA system. With professional analog I/O and easy pairing of Bluetooth-enabled devices such as mobile phones and tablets, the Nano KX seamlessly integrates into your production space to provide non-Bluetooth speakers with wireless playback capabilities. Plus, the easy-to-use knob allows you to control volume levels of your signal, as well as advance tracks, pause and mute devices connected via Bluetooth.

FEATURES

BLUETOOTH COMPATIBILITY

Because many high-end studio monitors, PA systems and mixers do not include Bluetooth connectivity, the JBL Nano KX is built to integrate Bluetooth functionality into those systems and provides wireless audio playback capabilities. With the Nano KX, you can wirelessly stream your tracks from your mobile phone, tablet, or computer through your non-Bluetooth speakers.

EASY SETUP, CONTROL AND OPERATION

Setting up and pairing devices to the Nano KX is easy. The controller's illuminated volume knob is perfect for low-light environments, and it also includes controls for play, pause, track advance and mute for Bluetooth connected devices.

SPECIFICATIONS

AUDIO INPUTS:	2x balanced/unbalanced XLR/TRS combo jacks
AUX INPUT:	1x 3.5mm mini jack connector
MAX INPUT LEVEL:	+10 dB
INPUT IMPEDANCE:	XLR/TRS combo >10K ohms 3.5mm mini jack >5K ohms
AUDIO OUTPUTS:	2x XLR male balanced connectors
AUX OUTPUT:	1x 3.5mm mini jack connector

PROFESSIONAL CONNECTIONS

With professional I/O connections, the Nano KX is designed to seamlessly integrate into your signal path. The Nano KX features two stereo XLR/TRS combo inputs and an auxiliary 3.5mm (1/8") TRS input for connecting your speakers and analog sources. The controller also includes three outputs—two XLR and an auxiliary 3.5mm—to connect to JBL NANO K Series monitors or other self-powered speaker systems.

COMPACT, SLEEK DESIGN

With its sleek design, the Nano KX looks right at home in any modern professional production space. And with its compact size, the controller won't get in the way or clutter your style.

MAX OUTPUT LEVEL:	> +10dB
IMPEDANCE:	0-5K ohm
FREQUENCY RANGE:	20Hz – 20kHz (+1dB / -1dB)
SIGNAL TO NOISE:	Better than -120dB
CHANNEL CROSSTALK:	> -95dB
DISTORTION:	<0.01%
DIMENSION (WXDXH):	116.5mm x 95mm x 95mm
NET WEIGHT / GROSS WEIGHT:	0.42 kg / 0.55 kg



HARMAN Professional 8500 Balboa Blvd. Northridge, CA 91329 USA

© 2019 HARMAN International Industries, Incorporated. All rights reserved.
Features, specifications and appearance are subject to change without notice.

www.jblpro.com