



VT4886 VT4883 V4 Crown I-Tech (26 dB Gain)



NAME	PRESET	DESCRIPTION	CH 1	CH 2
SHORT THROW PRESETS FOR 1x, 2x, 3x ENCLOSURES (USE FOR: DISTRIBUTED FRONT FILL, POLE / EXT ROD MOUNT, UNDERBALCONY, STACKED SIDEFILL/FOH)				
VT4886 1x FULLRANGE ST	1	Single enclosure: nominal flat	VT4886	VT4886
VT4886 2x FULLRANGE ST	2	Two enclosures: 60 Hz high pass filter; nominal flat HF for short throw applications	VT4886	VT4886
VT4886 2x 80 ST	3	* Two enclosures: 80 Hz high pass filter (for use with 4883 80); nominal flat HF	VT4886	VT4886
VT4886 2x 120 ST	4	* Two enclosures: 120 Hz high pass filter (for use with 4883 120); nominal flat HF	VT4886	VT4886
VT4886 2x 160 ST	5	* Two enclosures: 160 Hz high pass filter (for use with 4883 160); nominal flat HF	VT4886	VT4886
VT4886 2x 300 ST	6	* Two enclosures: 300 Hz high pass filter (for use with 4883 300); nominal flat HF	VT4886	VT4886
VT4886 3x FULLRANGE ST	7	Three enclosures: 60 Hz high pass filter; nominal flat HF for short throw applications	VT4886	VT4886
VT4886 3x 80 ST	8	* Three enclosures: 80 Hz high pass filter (for use with 4883 80); nominal flat HF	VT4886	VT4886
VT4886 3x 120 ST	9	* Three enclosures: 120 Hz high pass filter (for use with 4883 120); nominal flat HF	VT4886	VT4886
VT4886 3x 160 ST	10	* Three enclosures: 160 Hz high pass filter (for use with 4883 160); nominal flat HF	VT4886	VT4886
VT4886 3x 300 ST	11	* Three enclosures: 300 Hz high pass filter (for use with 4883 300); nominal flat HF	VT4886	VT4886
LONG THROW PRESETS (HF PRE-EMPHASIS FOR MEDIUM-LONG THROW APPLICATIONS)				
VT4886 FULLRANGE LT	12	Long Throw preset: 60 Hz high pass filter; HF pre-emphasis for medium-to-long throw applications	VT4886	VT4886
VT4886 80 LT	13	* Long Throw preset: 80 Hz high pass filter (for use with 4883 80); HF pre-emphasis	VT4886	VT4886
VT4886 120 LT	14	** Long Throw preset: 120 Hz high pass filter (for use with 4883 120); HF pre-emphasis	VT4886	VT4886
VT4886 160 LT	15	** Long Throw preset: 160 Hz high pass filter (for use with 4883 160); HF pre-emphasis	VT4886	VT4886
VT4886 300 LT	16	** Long Throw preset: 300 Hz high pass filter (for use with 4883 300); HF pre-emphasis	VT4886	VT4886
VT4883 PROCESSING : NON-CARDIOID CONFIGURATIONS (3 : 1 RATIO 4886 : 4883 = LF EXTENSION)				
VT4883 80	17	80 Hz low pass filter (for use with 4886 80 and - optional - 4881A, 4882, 4882 or 4880A X presets)	VT4883	VT4883
VT4883 120	18	120 Hz low pass filter (for use with 4886 120 and - optional - 4881A, 4882, 4882 or 4880A X presets)	VT4883	VT4883
VT4883 160	19	160 Hz low pass filter (for use with 4886 160 and - optional - 4881A, 4882, 4882 or 4880A X presets)	VT4883	VT4883
VT4883 300	20	300 Hz low pass filter (for use with 4886 300 and - optional - 4881A, 4882, 4882 or 4880A X presets)	VT4883	VT4883

- NOTES
- * Physically Separate configuration (VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)
Additional time delay required to account for geometric path difference between VT4886 and VT4883
Enable optional Input PEQ1 for use in Closely Coupled configurations (VT4886 stacked on top of VT4883 or suspended below VT4883)
 - ** Closely Coupled configuration (VT4886 stacked on top of VT4883 or suspended below VT4883)
Enable optional Input PEQ1 for use in Physically Separate configurations
(VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)