






THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HARMAN.
DO NOT DISCLOSE, REPRODUCE OR PUBLISH WITHOUT WRITTEN
HARMAN APPROVAL

REVISIONS						
CHG	LTR	DESCRIPTION	DRFT	CHK	DATE	APPR
11823	A	RELEASE FOR MARKETING	YT		11/12/13	



- COMPONENTS: LF - 2262HPL, HF - D2430K
90 x 50 PROGRESSIVE TRANSITION WAVEGUIDE
- INPUT/OUTPUT CONNECTIONS: 4 X NEUTRIK NL4
OPERATING MODE: BIAMP ONLY.
- GRILLE: 14 GA PERFORATED CRS, POWDERCOATED BLACK CLOTH BACKING.
- 18MM BIRCH PLYWOOD.
- FINISH: BLACK DURAFLEX.
- SUSPENSION POINTS: 14 X M10
- WEIGHT: 18.6 KG (41.0 LBS)
- CENTER OF GRAVITY (CG)
- POLE MOUNT DIA: 35MM
- DIMENSIONS ARE IN MM (INCHES)

NOTES: (UNLESS OTHERWISE SPECIFIED)

HARMAN		9500 Balboa Blvd Northridge, CA 91329 USA	
TITLE CUSTOMER DWG, VTX-F12			
SIZE D	DRAWING NO. 1000124332		REV A
SCALE: 1/1		SHEET 1 of 1	