






THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL INCORPORATED. THEY ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR MANUFACTURE OR APPARATUS WITHOUT WRITTEN PERMISSION.

ALL MATERIAL SPECIFIED ON THIS DRAWING SHALL COMPLY WITH EUROPEAN DIRECTIVE 2002/95/EC. **RoHS**

REVISIONS					
LTR	DESCRIPTION	DRFT	D.C	DATE	APPR
A	RELEASE TO MARKETING	TH			



5. INPUT CONNECTORS: 2X NEUTRIK NL4, 2X NEUTRIK NL8 ON THE REAR SIDE AND 1X NEUTRIK NL4 ON FRONT SIDE.

4. GRILL: 14 GA. PERFORATED CRS, POWDER COATED BLACK WITH BLACK ACOUSTICAL CLOTH BACKING.

3. COMPONENTS: LF - 2X 2267HPL

2. MATERIALS: BIRCH PLYWOOD.

1. FINISH: BLACK DURAFLEX

9. POLE MOUNT: 20mm THREADED POLE SOCKET.

8. RIGGING SYSTEM: INTEGRATED RIGGING HARDWARE TO CONNECT MULTIPLE VTX-S25, VTX-V20 ENCLOSURES AND ACCESSORY ARRAY FRAME.

7. WEIGHT: 65 Kg (143 LBS).

6. CENTER OF GRAVITY (CG)

NOTES: (UNLESS OTHERWISE SPECIFIED)

TOLERANCES
(UNLESS OTHERWISE SPECIFIED)

- X.XX ± .063 INCH
- X.X ± .125 INCH
- ANGULAR TOLERANCE OF 0°±30'
- FRACTIONAL DIMENSIONS ± 1/32
- DIMENSIONS ARE INCHES
- ALL DIMENSIONS ARE FINISHED DIMENSIONS
- DO NOT SCALE DRAWING

JBL JBL PROFESSIONAL
A Harman International Company
Northridge, California 91329 U.S.A.

TITLE
CUSTOMER DRAWING: VTX-S25

SIZE **A** DRAWING NO. 1000129851 REV **A**

SCALE 1:1 SHEET 1 OF 1