




THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL INCORPORATED. THEY ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASIS FOR MANUFACTURING OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

REVISIONS					
LTR	DESCRIPTION	DRFT	CHK	DATE	APPR
A					ATR



- NOTES: (UNLESS OTHERWISE SPECIFIED)
- Components: LF – 1x M115 15"; HF 1x 2412H driver on PT-DXXHF horn; passive crossover
  - Input Connectors: None – direct cable entry 20' 2 cond. cable included
  - Grill: (not shown) 18 ga. perforated stainless steel, vinyl-dipped gray, black foam backing & stainless steel mesh vapor barrier
  - Materials: 5/8" exterior grade Finnish birch plywood
  - Finish: Gray Fiberglass
  - Suspension Points: 14 total, M10 threads; bolt heads extend approximately 0.25" above surface of enclosure

TOLERANCES (UNLESS OTHERWISE SPECIFIED)	
.XX	± .063 INCH
.X	± .125 INCH
ANGULAR	± 030°
FRACTIONAL	± 1/32
• DIMENSIONS ARE INCHES	
• ALL DIMENSIONS ARE FINISHED DIMENSIONS	
• DO NOT SCALE DRAWING	

DRAWN BY		DATE
ATR		11/26/02
CHECKED		DATE
ENGR		DATE
SIZE	SCALE	DRAWING NO.
A	1:	

JBL Professional		JBL Custom Shop	
A Harman International Company		Northridge, California 91329, U.S.A.	
TITLE		AC2215/XX-WRX	
		Weather Resistant	
		2-Way Loudspeaker	
SHEET	1	OF	1
REV	A		