






THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL, INCORPORATED. THEY ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR MANUFACTURE OR APPARATUS WITHOUT WRITTEN PERMISSION.

ALL MATERIAL SPECIFIED ON THIS DRAWING SHALL COMPLY WITH EUROPEAN DIRECTIVE 2002/95/EC. **RoHS**



- NOTES:
1. DRIVERS: LF - 2265H 15", HF - 2432H MOUNTED ON A PT-HXHF WAVEGUIDE
 2. SUSPENSION: 12 X M10 STAINLESS FITTINGS
 3. FINISH: 0.060" THICK COARSE TEXTURE FIBERGLASS (NOT REFLECTED IN DIMENSIONS ABOVE)
 4. GRILLE: 20 GA STAINLESS STEEL VAPOR BARRIER
 5. INPUT: SEALED GLANDNUT WITH 20' 2 CONDUCTOR CAPTIVE CABLE
 6. COLOR: STD GRAY WHITE - WH AND BLACK - BL ARE AVAILABLE AT NO EXTRA COST

REVISIONS				
CHG	LTTR	DESCRIPTION	DEFT	D.C

TOLERANCES
(UNLESS OTHERWISE SPECIFIED)

X.XX ± .063 INCH
X.X ± .125 INCH

ANGULAR TOLERANCE OF 0°-30°
FRACTIONAL DIMENSIONS ± 1/32

• ALL DIMENSIONS ARE FINISHED DIMENSIONS
• DO NOT SCALE DRAWING

JBL JBL PROFESSIONAL
A Harman International Company
Northridge, California 91329 U.S.A.

TITLE
CUSTOMER DRAWING: AM7215-XX-WRX

SIZE **A** DRAWING NO. **A**

SCALE NTS SHEET 1 OF 1