


PART NO.		DESCRIPTION		REMARKS	
XXXXX-001		AM212/XX-VRX			


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL INCORPORATED THEY ARE NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT WRITTEN PERMISSION AS THE BASIS FOR MANUFACTURING OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION

ALL MATERIAL SPECIFIED IN THIS DRAWING SHALL COMPLY WITH EUROPEAN DIRECTIVE 2002/95/EC (RoHS)


REV. NO.		REVISIONS		DATE	
CHG	LTR	DESCRIPTION	DRAWN BY	DATE	APPROVED BY
---	---	PRELIMINARY RELEASE	---	---	---




Top/Bottom



Front



Sides



Rear

- NOTES:
1. DRIVERS: LF - 262H-1.12", HF - 2408H MOUNTED ON A PT-HXXHF WAVEGUIDE
  2. SUSPENSION: 14 X MID TREAD, BOLT HEAD EXTEND APPROX. 0.34" ABOVE SURFACE OF ENCLOSURE
  3. FINISH: 0.060" THICK COARSE TEXTURE FIBERGLASS (NOT REFLECTED IN DIMENSIONS ABOVE)
  4. GRILLE: 16 GA STAINLESS STEEL, WITH STAINLESS STEEL VAPOR BARRIER
  5. INPUT: SEALED GLANDNUT WITH 20' 2 CONDUCTOR CAPTIVE CABLE
  6. COLOR: STD GRAY; WHITE - WH AND BLACK -BL ARE AVAILABLE AT NO EXTRA COST

THIRD ANGLE PROJECTION

TOLERANCES UNLESS SPECIFIED

XXX DECIMALS

XXX FRACTIONAL 1/32

XXX DIMENSIONS ARE IN INCHES

XXX DIMENSIONS ARE IN MILLIMETERS

DATE

0.050

SHEET 1 OF 1

JBL PROFESSIONAL

Head Office, California, USA

AM212/XX-VRX