

4

3


2

1


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL INCORPORATED. THEY ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR MANUFACTURE OR APPARATUS WITHOUT WRITTEN PERMISSION.

ALL MATERIAL SPECIFIED ON THIS DRAWING SHALL COMPLY WITH EUROPEAN DIRECTIVE 2002/95/EC. RoHS


REVISIONS					
CHG	LTR	DESCRIPTION	DRFT	D.C	DATE
	A	RELEASE	SO		




TOP/BOT



FRONT



SIDES



REAR

- COMPONENTS: LF – 1X 226J 6" WOOFER
HF – 1X 2414H COMPRESSION DRIVER
1X PTB-99HF-1 WAVEGUIDE.
- INPUT CONNECTORS: 2M (6 FT) 2 CONDUCTOR 18AWG CAPTIVE DIRECT BURIAL CABLE.
- OPERATING MODE: FULLY PASSIVE CROSSOVER.
- GRILLE: 16 GA. PERFORATED STAINLESS STEEL, VINYL DIP, WITH BLACK FOAM BACKING AND SS VAPOR BARRIER.
- MATERIALS: 12MM (.47") HARDWOOD PLYWOOD
TOP/BTM PANEL 15MM (.59") HARDWOOD PLYWOOD
- FINISH: GRAY FIBERGLASS (WHITE & BLACK AVAILABLE)
- WEIGHT: 7.6 Kg (16.8 LBS).
- INDICATES CENTER OF GRAVITY (CG) ⊕
- SUSPENSION POINTS " " 8 TOTAL:
1 EA M8 THREAD PATTERN – TOP/BTM PANEL
2 EA M8 THREAD PATTERN – REAR PANEL
4 EA M6 THREAD PATTERN – REAR PANEL

NOTES: (UNLESS OTHERWISE SPECIFIED)

TOLERANCES (UNLESS OTHERWISE SPECIFIED)

- X.XX +/- .063 INCH
- X.X +/- .125 INCH
- ANGULAR TOLERANCE OF 0 +/- 30°
- FRACTIONAL DIMENSIONS +/- 1/32
- DIMENSIONS ARE INCHES
- ALL DIMENSIONS ARE FINISHED DIMENSIONS
- DO NOT SCALE DRAWING



JBL PROFESSIONAL
A Harman International Company
Northridge, California 91329 U.S.A.

TITLE
CUSTOMER DWG: AC16-WRX

SIZE A DRAWING NO. REV A

SCALE NTS SHEET 1 OF 1