

# MTC-48TRx12

Professional Series – Tile Rail for 4' x 4' Ceiling Tiles



## Key Features:

- Accessory tile rail for installing many of JBL's ceiling loudspeakers into 4 ft by 4 ft (1200 x 1200 mm; 48 x 48 inch) ceiling tiles in suspended ceiling applications
- Can be used with any JBL ceiling speakers having the C-ring/tile-rail mounting system, including (at product release):
  - Control 24C/CT Micro & 24CT MicroPlus
  - Control 24C/CT, 26C/CT, 19CS/CST
  - Control 47C/T, 47LP, 47HC, 40CS/T, 42C
  - Control 226C/T
  - 8124/8128
  - Not for JBL speakers that install with tile bridges (such as CSS Series, 8138, C227C/CT, C300 Series models). Check with JBL Professional Customer Service for most up-to-date compatibility list
- Inverted V-groove provides support to the tile rail grid in case of tile failure while reducing vibration transfer to—and rattling from—ceiling tile grid system
- 1.2 mm (0.05 in) metal thickness provides the additional support required by the long span
- Multiple C-ring mounting holes
- Additional hole locations drillable by installer
- One MTC-48TRx12 contains a pack of 12 tile rails, enough for 6 speakers (2 per speaker)



## Specifications:

Material	1.2 mm (0.05 in, 18 gauge) galvanized steel, SECC
C-Ring Mounting Holes	30 holes; additional hole locations drillable by installer
Dimensions	27 mm (1.1 in) tall x 30 mm (1.2 in) wide x 1267 mm (49.9 in) total length to extend beyond tile grids. 1219 mm (48.0 in) between top of inverted v-grooves, to line up with tile grids.

JBL continually engages in research related to product improvement. Changes introduced into existing products without notice are an expression of that philosophy.

## Mounting Dimensions:

Dimensions in inches (mm)

