

**JBL Professional**  
**PD5212 /43/64/95**  
**BSS London Architect Macros**

<b>PD5212/43 Bi-Amp</b>			
	LF	MF	HF
Low Shape	BW24		BW24
Low Freq	76.8 Hz		893 Hz
High Shape	BW18		
High Freq	943 Hz		Out
Phase	0 Degrees		0 Degrees
Polarity	Normal		Normal
Gain	-7.00 dB		-15.00 dB
Delay	0.000 mS		1.000 mS
<b>LF EQ</b>			
High Shelf	215 Hz	12 dB/Oct	-9.00 dB
Bell	310 Hz	0.33 Oct	+2.00 dB
Bell	680 Hz	0.70 Oct	-5.00 dB
Bell	160 Hz	0.33 Oct	-2.00 dB
<b>MF EQ</b>			
<b>HF EQ</b>			
Bell	2.70 kHz	1.60 Oct	-5.80 dB
Bell	18.00 kHz	0.60 Oct	+2.60 dB
Bell	1.50 kHz	1.00 Oct	-2.50 dB
Bell	5.00 kHz	0.80 Oct	-2.80 dB
High Shelf	20.0 Hz	15 dB/Oct	-2.20 dB
<b>PD5212/43 Passive</b>			
	LF	MF	HF
Low Shape	BW24		
Low Freq	77.0 Hz		
High Shape			
High Freq	Out		
Phase	0 Degrees		
Polarity	Normal		
Gain	-7.30 dB		
Delay	0.000 mS		
<b>LF EQ</b>			
<b>M/HF EQ</b>			
High Shelf	215 Hz	12 dB/Oct	-9.50 dB
Bell	300 Hz	0.50 Oct	+4.00 dB
Bell	1.00 kHz	0.15 Oct	+2.00 dB
Bell	4.90 kHz	0.45 Oct	-1.00 dB

<b>PD5212/64 Bi-Amp</b>			
	LF	MF	HF
Low Shape	BW24		BW24
Low Freq	76.8 Hz		780 Hz
High Shape	BW24		
High Freq	961 Hz		Out
Phase	0 Degrees		0 Degrees
Polarity	Normal		Inverted
Gain	-6.50 dB		-12.00 dB
Delay	0.000 mS		1.208 mS
<b>LF EQ</b>			
High Shelf	215 Hz	15 dB/Oct	-8.50 dB
Bell	614 Hz	0.45 Oct	-5.20 dB
<b>MF EQ</b>			
<b>HF EQ</b>			
Low Shelf	5.00 kHz	12 dB/Oct	-11.50 dB
Bell	1.00 kHz	0.50 Oct	+3.30 dB
Bell	1.70 kHz	0.33 Oct	-2.20 dB
<b>PD5212/64 Passive</b>			
	LF	MF	HF
Low Shape	BW24		
Low Freq	77.0 Hz		
High Shape			
High Freq	Out		
Phase	0 Degrees		
Polarity	Normal		
Gain	-6.60 dB		
Delay	0.000 mS		
<b>LF EQ</b>			
<b>M/HF EQ</b>			
High Shelf	215 Hz	15 dB/Oct	-7.60 dB
Bell	600 Hz	0.45 Oct	-2.00 dB
Bell	1.70 kHz	0.30 Oct	-1.00 dB
Bell	4.50 kHz	0.30 Oct	-1.50 dB

<b>PD5212/95 Bi-Amp</b>			
	LF	MF	HF
Low Shape	BW24		BW24
Low Freq	76.7 Hz		840 Hz
High Shape	BW24		
High Freq	944 Hz		Out
Phase	0 Degrees		0 Degrees
Polarity	Normal		Normal
Gain	-5.00 dB		-14.30 dB
Delay	0.000 mS		1.344 mS
<b>LF EQ</b>			
High Shelf	280 Hz	15 dB/Oct	-13.00 dB
Bell	500 Hz	0.50 Oct	+2.00 dB
Bell	320 Hz	0.33 Oct	-1.50 dB
<b>MF EQ</b>			
<b>HF EQ</b>			
Low Shelf	5.00 kHz	12 dB/Oct	-6.30 dB
Bell	2.50 kHz	1.60 Oct	-2.00 dB
Bell	1.40 kHz	0.20 Oct	-1.50 dB
Bell	1.00 kHz	0.50 Oct	+2.50 dB
<b>PD5212/95 Passive</b>			
	LF	MF	HF
Low Shape	BW24		
Low Freq	77.0 Hz		
High Shape			
High Freq	Out		
Phase	0 Degrees		
Polarity	Normal		
Gain	-3.60 dB		
Delay	0.000 mS		
<b>LF EQ</b>			
<b>M/HF EQ</b>			
High Shelf	280 Hz	15 dB/Oct	-9.00 dB
Bell	320 Hz	0.50/Oct	-3.00 dB
Bell	870 Hz	0.20/Oct	-2.00 dB
Bell	1.00 kHz	0.30/Oct	+2.50 dB