


PART NO.	DESCRIPTION	REMARKS
XXXX-001	ACE212/XX	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL, INCORPORATED. THEY ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED, COPIED, OR USED AS THE BASIS FOR MANUFACTURING OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ALL MATERIAL SPECIFIED ON THIS DRAWING SHALL COMPLY WITH EUROPEAN DIRECTIVE 2002/95/EC (ROHS)

CHG	TR	DESCRIPTION	DRT	CHK	DATE	APP
---	A	Production				



- NOTES:
1. DRIVERS: LF - M12-8 12" HF - 2412/MTM MOUNTED ON A PT-FXXHF WAVEGUIDE
  2. SUSPENSION: 15 X M10 THREAD, 4 M8 ON REAR FOR THIRD PARTY MOUNT (SEE SPEC SHEET)
  3. FINISH: 0.060" THICK COARSE TEXTURE DURAFLEX (NOT REFLECTED IN DIMENSIONS ABOVE)
  4. GRILLE: 14 GA POWDER COATED PREFRATED STEEL
  5. INPUT: NEUTRIK SPEAKON®, CE COMPLIANT COVERED BARRIER STRIP
  6. COLOR: BLACK OR WHITE (ON REQUEST)

TOLERANCES: UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
FRACTIONAL 1/32  
DECIMAL .001  
HOLE SIZE .0015

THIRD ANGLE PROJECTION

TITLE: JBL PROFESSIONAL  
AC2212/XX

DATE: 11/11/11

REV: 1

SHEET 1 OF 1