

JBL Professional
PD5200 /43/64/95
BSS London Architect Macros

PD5200/43 Bi-Amp			
	LF	MF	HF
Low Shape		BW24	BW18
Low Freq		233 Hz	1.99 kHz
High Shape		BW18	
High Freq		1.88 kHz	Out
Phase		0 Degrees	0 Degrees
Polarity		Normal	Inverted
Gain		-10.00 dB	-15.00 dB
Master		-10.00 dB	
Delay		0.000 mS	0.563 mS
LF EQ			
MF EQ			
Bell	300 Hz	0.50 Oct	+4.00 dB
Bell	1.20 kHz	0.50 Oct	+2.00 dB
Bell	1.90 kHz	0.33 Oct	-3.00 dB
HF EQ			
Bell	15.00 kHz	0.58 Oct	+11.00 dB
Bell	2.23 kHz	0.50 Oct	+2.00 dB
High Shelf	20.0 Hz	15 dB/Oct	-1.00 dB
PD5200/43 Passive			
	LF	MF	HF
Low Shape		BW24	
Low Freq		235 Hz	
High Shape			
High Freq		Out	
Phase		0 Degrees	
Polarity		Normal	
Gain		-15.00 dB	
Delay		0.000 mS	
LF EQ			
M/HF EQ			
Bell	12.00 kHz	1.40 Oct	-2.70 dB
Bell	19.00 kHz	0.40 Oct	+8.50 dB
Bell	750 Hz	0.80 Oct	-1.50 dB
Bell	1.50 kHz	0.33 Oct	+2.00 dB
High Shelf	20.0 Hz	15 dB/Oct	-2.00 dB

PD5200/64 Bi-Amp			
	LF	MF	HF
Low Shape		BW24	BW24
Low Freq		208 Hz	2.12 kHz
High Shape		BW 24	
High Freq		1.49 kHz	
Phase		0 Degrees	0 Degrees
Polarity		Normal	Normal
Gain		-2.70 dB	-10.00 dB
Master		-10.00 dB	
Delay		0.000 mS	.948 mS
LF EQ			
MF EQ			
Bell	750 Hz	1.30 Oct	-6.00 dB
Bell	300 Hz	0.35 Oct	-2.20 dB
HF EQ			
Bell	2.80 kHz	0.45 Oct	-3.30 dB
Bell	12.00 kHz	0.65 Oct	+3.70 dB
Bell	4.00 kHz	1.00 Oct	-1.50 dB
PD5200/64 Passive			
	LF	MF	HF
Low Shape		BW24	
Low Freq		210 Hz	
High Shape			
High Freq		Out	
Phase		0 Degrees	
Polarity		Normal	
Gain		-13.00 dB	
Delay		0.000 mS	
LF EQ			
M/HF EQ			
High Shelf	250 Hz	12 dB/Oct	-4.00 dB
Bell	550 Hz	0.33 Oct	-1.50 dB
Bell	4.81 kHz	1.00 Oct	-1.60 dB
Bell	310 Hz	0.50 Oct	-2.00 dB

PD5200/95 Bi-Amp			
	LF	MF	HF
Low Shape		BW24	BW48
Low Freq		205 Hz	2.12 kHz
High Shape		BW24	
High Freq		1.69 kHz	Out
Phase		0 Degrees	0 Degrees
Polarity		Normal	Normal
Gain		-4.00 dB	-11.30 dB
Master		-10.0 dB	
Delay		0.000 mS	.198 mS
LF EQ			
MF EQ			
Bell	640 Hz	1.20 Oct	-4.10 dB
Bell	240 Hz	0.60 Oct	-3.50 dB
Bell	1.40 kHz	0.33 Oct	+2.50 dB
HF EQ			
Bell	15.00 kHz	1.45 Oct	+7.60 dB
Bell	2.10 kHz	0.14 Oct	+2.80 dB
Bell	2.60 kHz	0.27 Oct	-1.90 dB
Bell	8.10 kHz	0.80 Oct	-1.90 dB
PD5200/95 Passive			
	LF	MF	HF
Low Shape		BW24	
Low Freq		205 Hz	
High Shape			
High Freq		Out	
Phase		0 Degrees	
Polarity		Normal	
Gain		-15.00dB	
Delay		0.000 mS	
LF EQ			
M/HF EQ			
High Shelf	300 Hz	12 dB/Oct	-1.00 dB
Bell	19.00 kHz	0.40 Oct	+9.00 dB
Bell	1.80 kHz	0.75 Oct	+1.80 dB
Bell	12.00 kHz	1.40 Oct	-3.00 dB
High Shelf	20.0 Hz	15 dB/Oct	-2.00 dB