

PRX915XLF

Professional Powered 15-Inch Subwoofer

JBL


PROFESSIONAL
by HARMAN

SPEC SHEET



OVERVIEW

The **PRX915XLF subwoofer**, part of the JBL PRX900 Series powered loudspeakers and subwoofers, takes professional portable PA performance to a new level with advanced acoustics, comprehensive DSP, unrivaled power performance and durability, and complete BLE control via the JBL Pro Connect app.



PRODUCT HIGHLIGHTS

- **Transducers:**
 - 915SG 15" ferrite magnet woofer with 3" voice-coil
- **Low-noise, low-distortion gain** staging design
- Lightweight, efficient **Class D amplification**
- **Power:** 2,000 watts peak/1,000 watts RMS
- **Frequency response:** 36 Hz–98 Hz @2π (-10 dB); 40 Hz–87 Hz @2π (-3 dB)
- **Max SPL:** 131 dB
- **Color LCD screen** provides access to comprehensive DSP suite
- **DriveRack Technology** includes Automatic Feedback Suppression, system limiter and 20ms of speaker delay in 100-microsecond intervals for time-aligned systems
- **Optimized presets** for pairing full-range speakers with subwoofers
- **Quiet fanless** operation
- **JBL Pro Connect app** allows full system control of up to 10 speakers and line integration with JBL EON ONE MK2, PRX ONE, and EON700 systems
- **BLE networking** via JBL Pro Connect app
- **18mm birch cabinet** features optimized bracing for smooth low-frequency response
- **I/Os:**
 - 2 XLR balanced Combo jacks
 - 2 XLR pass-through outs
- **Two integrated handles** (top and side)
- **Mount:** M20 pole cup
- **Ultra-low system latency:** <1ms
- **Net weight:** 28.6 kg (63 lbs); **Gross weight:** 33.6 kg (74 lbs)
- **Dimensions:** 549 x 480 x 580 mm (21.6 x 18.9 x 22.8 in)
- **Shipping dimensions:** 588 x 592 x 692 mm (23.1 x 23.3 x 27.2 in)
- Backed by **industry-leading seven-year warranty**

PRX915XLF

Professional Powered 15-Inch Subwoofer



SPEC SHEET

SPECIFICATIONS

System Type	15-Inch Powered Subwoofer
Woofers Model	915SG
Woofers Size	15"
Woofers Magnet	Ferrite
Woofers Voice Coil	3"
Transducer Impedance	Rated: 4 Ω
Max SPL	131 dB @ 1m/2 π
Freq Range -10	36 Hz - 98 Hz (2 π)
Freq Range -3	40 Hz - 87 Hz (2 π)
Hor Dispersion	Omni
Vert Dispersion	Omni
Crossover Frequency	80Hz, 100Hz, 120Hz Selectable
Power Rating	2000W Peak / 1000W RMS

AC Power Input	100-230Vrms 50-60Hz
Cooling	Natural Convection No Fan
LED Indicators	Limit, 2x SSM Input
Input Impedance	100K Ω Balanced
Input Gain	0-12dB Gain
I/O	x2 Combo Inputs x2 XLR Pass Through Outputs
Cabinet	18mm Plywood + Duraflex
Grille	Powder coated steel, T=1.5mm
Suspension/Mount	Pole Mount on Top Surface
Handles	Side Handle x2
Net Weight	28.6kg (63 lbs)
Gross Weight	33.6 kg (74 lbs)
Product Dims	549 x 480 x 580 mm (21.6 x 18.9 x 22.8 in)
Shipping Dims	588 x 592 x 692 mm (23.1 x 23.3 x 27.2 in)

PRODUCT FEATURES

All-New Acoustic Designs

From cone to cabinet, the PRX915XLF is designed for advanced acoustic performance. A next-generation 915SG woofer with ferrite magnet delivers smooth, natural bass response, and an FEA flared port design reduces air noise and distortion. It all adds up to clean, accurate, powerful sound at any volume.

Power That Performs for You

PRX900 systems effortlessly support large performance spaces with high power and performance needs. Driven by highly efficient 2,000W (peak) Class D power amps, the PRX915XLF delivers bass with clarity and definition at maximum volume. High-quality, high-linearity inductors deliver high power efficiency and low total harmonic distortion. High-quality DACs and ADCs provide near-lossless audio conversion. And with a full-bandwidth CMRR (Common Mode Rejection Ratio) greater than 55 dB and THD (total harmonic distortion) rating of <32 dB, noise is virtually nonexistent.

Dial In Your Sound With Class-Leading DSP

The PRX915XLF's class-leading DSP package, accessible via onboard LCD or the JBL Pro Connect app, includes 6-band parametric EQ for system tuning and nuanced tonal control, plus lowpass filter and 20ms delay.

Versatile and Scalable

Combine PRX900 Series loudspeakers and subwoofers in a range of configurations to meet the needs of both mobile scenarios and fixed installs. Subwoofers feature M20 pole cups.

Part of the Pro Connect Ecosystem

JBL's Pro Connect app offers BLE functionality for system control of up to 10 speakers and line integration with JBL EON ONE MK2, PRX ONE, and EON700 loudspeakers. Access full DSP functions anywhere right from the app, including app-only features like speaker snapshots and groupings.

Rugged and Road-Worthy

PRX900 components are housed in strong, lightweight cabinets that maximize both acoustic performance and durability. The PRX915XLF enclosure is built from 18mm birch, with optimized bracing that smooths out low-frequency response. A Duraflex coating provides superior durability.

In It for the Long Haul

Like every JBL product, the PRX915XLF undergoes an industry-leading 100-hour stress test of all components to ensure systems perform beyond expectations in real-world scenarios. It's so reliable that it's backed with an unprecedented seven-year warranty.

PRX915XLF

Professional Powered 15-Inch Subwoofer



SPEC SHEET

PRODUCT DIMENSIONS ■



HARMAN Professional 8500 Balboa Blvd. Northridge, CA 91329 USA

© 2022 HARMAN International Industries, Incorporated. All rights reserved.
Features, specifications and appearance are subject to change without notice.

www.jblpro.com

Issued: 9/2022