

Mounting Brackets for JBL Professional LSR6300, LSR4300, LSR2300 Series Studio Monitors

Mounting brackets are available from Omnimount

To find sources for Omnimount in your area, please send an email to

info@omnimount.com. Or call Omnimount at (480) 829-8000

For detailed model information, visit the Omnimount Website: www.omnimount.com/pro

Click on Audio Mounts, and click on the models specified below.

Omnimount Model Numbers for JBL Studio Monitors:

LSR6328P – Mounting points on bottom of speaker

- Wall brackets: Omnimount Model 60.0 WB (10.75 inches) or Omnimount 60.0 WBX 18 inches
- Requires four screws with M6 metric thread, that are no shorter than 1.5” (38.1mm) in length plus the thickness of the mounting bracket plate. Maximum length of the screw should not exceed 2” (50.8 mm) plus the thickness of the mounting bracket.
- 4 mm (or 5/32”) Allen wrench is required to remove factory-supplied screws.

LSR63332, LSR6312SP – Mounting points on rear of speaker

- Wall brackets: Omnimount Model 60.0 WA
- Ceiling brackets (Allow horizontal orientation but not vertical orientation)
Omnimount 60.0 CA (13 1/8th inches length from ceiling.)
- Requires four screws with M6 metric thread, that are no shorter than 1.5” (38.1mm) in length plus the thickness of the mounting bracket plate. Maximum length of the screw should not exceed 2” (50.8 mm) plus the thickness of the mounting bracket.
- 4 mm (or 5/32”) Allen wrench is required to remove factory-supplied screws.

LSR4328P, LSR4326P, LSR2328P, LSR2325P

– Mounting points on bottom of speaker

- Wall Brackets: Omnimount Model 30.0 WB (9.75 inches) or Omnimount 30.0 WBX (14.75 inches)
- Requires four screws with M6 metric thread, that are no shorter than 1.5” (38.1mm) in length plus the thickness of the mounting bracket plate. Maximum length of the screw should not exceed 2” (50.8 mm) plus the thickness of the mounting bracket.

LSR6325P-1, LSR6325P, LSR25P - Mounting points on rear of speaker

- Wall Brackets: Omnimount Model 30.0 WA.
- Ceiling Mount Omnimount 30.0 CA (10.25 inches length from ceiling)
- Requires four screws, 1/4” in diameter, with 20 threads per inch, and a length of 1/2” plus the thickness of the mounting bracket plate.