



VT4886 VT4883 VT4880A V4 PRESETS

BSS AUDIO FDS-366T Omnidrive Compact Plus



ROUTING	INPUT A	INPUT B	INPUT C					FILTERS AVAIL
PRESET	OUT 1	OUT 2	OUT 3	OUT 4	OUT 5	OUT 6		
BLANK (USER)	1	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

3x VT4886 SHORT THROW + VT4880A + VT4883 *

NON-CARDIOID CONFIGURATIONS

X 80 ST	2	VT4880A X	VT4883 80	3x VT4886 ST 80	VT4880A X	VT4883 80	3x VT4886 ST 80	1
X 160 ST	3	VT4880A X	VT4883 160	3x VT4886 ST 160	VT4880A X	VT4883 160	3x VT4886 ST 160	1
X 300 ST	4	VT4880A X	VT4883 300	3x VT4886 ST 300	VT4880A X	VT4883 300	3x VT4886 ST 300	1
60 120 ST	5	VT4880A 60	VT4883 60-120	3x VT4886 ST 120	VT4880A 60	VT4883 60-120	3x VT4886 ST 120	1
60 160 ST	6	VT4880A 60	VT4883 60-160	3x VT4886 ST 160	VT4880A 60	VT4883 60-160	3x VT4886 ST 160	1
60 300 ST	7	VT4880A 60	VT4883 60-300	3x VT4886 ST 300	VT4880A 60	VT4883 60-300	3x VT4886 ST 300	1
BLANK (USER)	8	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

3x VT4886 SHORT THROW + VT4880A + VT4883 CARDIOID C1 *

CARDIOID CONFIGURATION 1 (HORIZONTAL = + - +)

C1 80 ST	9	VT4880A X	VT4883 FRONT 80	VT4883 REAR C1 80	3x VT4886 ST 80			20
C1 160 ST	10	VT4880A X	VT4883 FRONT 160	VT4883 REAR C1 160	3x VT4886 ST 160			18
C1 300 ST	11	VT4880A X	VT4883 FRONT 300	VT4883 REAR C1 300	3x VT4886 ST 300			17
BLANK (USER)	12	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

3x VT4886 SHORT THROW + VT4880A + VT4883 CARDIOID C2 *

CARDIOID CONFIGURATION 2 (VERTICAL BOTTOM-TO-TOP = - + +)

C2 80 ST	13	VT4880A X	VT4883 FRONT 80	VT4883 REAR C2 80	3x VT4886 ST 80			19
C2 160 ST	14	VT4880A X	VT4883 FRONT 160	VT4883 REAR C2 160	3x VT4886 ST 160			18
C2 300 ST	15	VT4880A X	VT4883 FRONT 300	VT4883 REAR C2 300	3x VT4886 ST 300			16
BLANK (USER)	16	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

3x VT4886 SHORT THROW + VT4880A + VT4883 CARDIOID C3 *

CARDIOID CONFIGURATION 3 (VERTICAL BOTTOM-TO-TOP = + - +)

C3 80 ST	17	VT4880A X	VT4883 FRONT 80	VT4883 REAR C3 80	3x VT4886 ST 80			19
C3 160 ST	18	VT4880A X	VT4883 FRONT 160	VT4883 REAR C3 160	3x VT4886 ST 160			18
C3 300 ST	19	VT4880A X	VT4883 FRONT 300	VT4883 REAR C3 300	3x VT4886 ST 300			17
BLANK (USER)	20	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	1
BLANK (USER)	21	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

* Physically Separate configuration (VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)
 Additional time delay required to account for geometric path difference between VT4886 and VT4883
 OPTIONAL EQ: 233 Hz / +4.4 dB / 0.20 oct for use in Closely Coupled configurations (VT4886 stacked on top of VT4883 or suspended below VT4883)

VT4886 LONG THROW + VT4880A + VT4883

NON-CARDIOID CONFIGURATIONS

X 80 LT **	22	VT4880A X	VT4883 80	VT4886 LT 80	VT4880A X	VT4883 80	VT4886 LT 80	1
X 160 LT ***	23	VT4880A X	VT4883 160	VT4886 LT 160	VT4880A X	VT4883 160	VT4886 LT 160	1
X 300 LT ***	24	VT4880A X	VT4883 300	VT4886 LT 300	VT4880A X	VT4883 300	VT4886 LT 300	1
60 120 LT ***	25	VT4880A 60	VT4883 60-120	VT4886 LT 120	VT4880A 60	VT4883 60-120	VT4886 LT 120	1
60 160 LT ***	26	VT4880A 60	VT4883 60-160	VT4886 LT 160	VT4880A 60	VT4883 60-160	VT4886 LT 160	1
60 300 LT ***	27	VT4880A 60	VT4883 60-300	VT4886 LT 300	VT4880A 60	VT4883 60-300	VT4886 LT 300	1
BLANK (USER)	28	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

VT4886 LONG THROW + VT4880A + VT4883 CARDIOID C1

CARDIOID CONFIGURATION 1 (HORIZONTAL = + - +)

C1 80 LT **	29	VT4880A X	VT4883 FRONT 80	VT4883 REAR C1 80	VT4886 LT 80			20
C1 160 LT ***	30	VT4880A X	VT4883 FRONT 160	VT4883 REAR C1 160	VT4886 LT 160			18
C1 300 LT ***	31	VT4880A X	VT4883 FRONT 300	VT4883 REAR C1 300	VT4886 LT 300			17
BLANK (USER)	32	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

VT4886 LONG THROW + VT4880A + VT4883 CARDIOID C2

CARDIOID CONFIGURATION 2 (VERTICAL BOTTOM-TO-TOP = - + +)

C2 80 LT **	33	VT4880A X	VT4883 FRONT 80	VT4883 REAR C2 80	VT4886 LT 80			19
C2 160 LT ***	34	VT4880A X	VT4883 FRONT 160	VT4883 REAR C2 160	VT4886 LT 160			18
C2 300 LT ***	35	VT4880A X	VT4883 FRONT 300	VT4883 REAR C2 300	VT4886 LT 300			16
BLANK (USER)	36	FLAT	FLAT	FLAT	FLAT	FLAT	FLAT	51

VT4886 LONG THROW + VT4880A + VT4883 CARDIOID C3

CARDIOID CONFIGURATION 3 (VERTICAL BOTTOM-TO-TOP = + - +)

C3 80 LT **	37	VT4880A X	VT4883 FRONT 80	VT4883 REAR C3 80	VT4886 LT 80			19
C3 160 LT ***	38	VT4880A X	VT4883 FRONT 160	VT4883 REAR C3 160	VT4886 LT 160			18
C3 300 LT ***	39	VT4880A X	VT4883 FRONT 300	VT4883 REAR C3 300	VT4886 LT 300			17

** Physically Separate configuration (VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)
 Additional time delay required to account for geometric path difference between VT4886 and VT4883
 OPTIONAL EQ: 233 Hz / +4.4 dB / 0.20 oct for use in Closely Coupled configurations (VT4886 stacked on top of VT4883 or suspended below VT4883)

*** Closely Coupled configuration (VT4886 stacked on top of VT4883 or suspended below VT4883)
 OPTIONAL EQ: 233 Hz / -4.4 dB / 0.20 oct for use in Physically Separate configurations
 (VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)