

REVISIONS				
CHG	LTR	DESCRIPTION	DATE	APPR
30258	A	RELEASE TO MARKETING	9/5/2003	AR
38767	B	ADDED DOCUMENT NUMBER		

Technical drawing of a tapered shaft. The drawing shows a shaft with a 30° taper. Key dimensions are provided in inches (top) and millimeters (bottom):


- Total length: 705.4 [2778]
- Distance from top to first step: 622.3 [2451]
- Distance from top to second step: 355.6 [1400]
- Distance from top to third step: 79.4 [311]
- Distance from top to fourth step: 130.2 [511]
- Distance from top to fifth step: 275.7 [1091]
- Distance from top to sixth step: 130.2 [511]
- Distance from top to seventh step: 275.7 [1091]
- Distance from top to eighth step: 562.1 [2211]
- Distance from top to ninth step: 122.1 [4805]

The shaft is labeled "R12.7 TYP" and "R0.5". The drawing is oriented vertically with "TOP" at the top and "BOTTOM SAME" at the bottom.

SIDES

REAR

1.6

- ⑧ CENTER OF GRAVITY (CG) 
- NOTES: (UNLESS OTHERWISE SPECIFIED)

JBL PROFESSIONAL
A Harman International Company
Northridge, California 91329 U.S.A.

PD5212/95

SIZE	DRAWING NO.	REV
A	444225	D

A	444363	D
---	--------	---

1