



VT4883 VT4886 SHORT THROW MIXED V4 Crown I-Tech (26 dB Gain)



NAME	PRESET	DESCRIPTION	CH 1	CH 2
MIXED 4883 / 4886 SHORT THROW PRESETS FOR 3x ENCLOSURES (USE FOR: DISTRIBUTED FRONT FILL, POLE / EXT ROD MOUNT, UNDERBALCONY, STACKED SIDEFILL/FOH)				
VT4883 80 VT4886 2x ST	1	* Two enclosures: 80 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
VT4883 120 VT4886 2x ST	2	* Two enclosures: 120 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
VT4883 160 VT4886 2x ST	3	* Two enclosures: 160 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
VT4883 300 VT4886 2x ST	4	* Two enclosures: 300 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
	5	INTENTIONALLY BLANK		
VT4883 60-120 VT4886 2x ST	6	* Two enclosures: 120 Hz crossover point; nominal flat HF; for use with 4881A, 4882, 4880 or 4880A 60	VT4883	VT4886
VT4883 60-160 VT4886 2x ST	7	* Two enclosures: 160 Hz crossover point; nominal flat HF; for use with 4881A, 4882, 4880 or 4880A 60	VT4883	VT4886
VT4883 60-300 VT4886 2x ST	8	* Two enclosures: 300 Hz crossover point; nominal flat HF; for use with 4881A, 4882, 4880 or 4880A 60	VT4883	VT4886
	9	INTENTIONALLY BLANK		
MIXED 4883 / 4886 SHORT THROW PRESETS FOR 3x ENCLOSURES (USE FOR: DISTRIBUTED FRONT FILL, UNDERBALCONY, STACKED SIDEFILL/FOH)				
VT4883 80 VT4886 3x ST	10	* Three enclosures: 80 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
VT4883 120 VT4886 3x ST	11	* Three enclosures: 120 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
VT4883 160 VT4886 3x ST	12	* Three enclosures: 160 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
VT4883 300 VT4886 3x ST	13	* Three enclosures: 300 Hz crossover point; nominal flat HF (optional: use with 4881A, 4882, 4880 or 4880A X)	VT4883	VT4886
	14	INTENTIONALLY BLANK		
VT4883 60-120 VT4886 3x ST	15	* Three enclosures: 120 Hz crossover point; nominal flat HF; for use with 4881A, 4882, 4880 or 4880A 60	VT4883	VT4886
VT4883 60-160 VT4886 3x ST	16	* Three enclosures: 160 Hz crossover point; nominal flat HF (for use with 4881A, 4882, 4880 or 4880A 60)	VT4883	VT4886
VT4883 60-300 VT4886 3x ST	17	* Three enclosures: 300 Hz crossover point; nominal flat HF (for use with 4881A, 4882, 4880 or 4880A 60)	VT4883	VT4886

NOTES * *Physically Separate configuration (VT4886 + UB-1 + SS5-BK extension rod + VT4883 or flown VT4886 + ground stacked VT4883)
Additional time delay required to account for geometric path difference between VT4886 and VT4883
Enable optional Input PEQ1 for use in Closely Coupled configurations (VT4886 stacked on top of VT4883 or suspended below VT4883)*