



REVISIONS					
LTR	DESCRIPTION	DRFT	D.C	DATE	APPR
A	INITIAL RELEASE	TH		4/24/18	
B	DIM 59.7 WAS 57.0	TH		3/12/19	
C	REVISED TOLERANCE FOR SUSPENSION POINT DIMENSIONS.	TH		5/9/19	
D	REVISED CG DIMENSIONS	TH		9/11/19	
E	ADD NOTES 9&10, UPDATE NOTES 3&5	MM		9/25/20	

- COMPONENTS: LF- 2X 2265H : MF- 4X 2169H : HF- 6X 2432H
- INPUT CONNECTORS: BARRIER STRIP TERMINAL (FOR #6 SPADE LUG)
- GRILLE 16GA, STANDARD VERSION: COLD ROLLED STEEL WITH CLOTH BACKING
WEATHER RESISTANT VERSIONS (WRC, WRX): STAINLESS STEEL WITH CLOTH AND STAINLESS STEEL MESH BACKING
- MATERIALS: EXTERIOR GRADE BIRCH PLYWOOD
- FINISH: STANDARD VERSION: BLACK DURAFLEX, WHITE AND GRAY AVAILABLE
WEATHER RESISTANT VERSION (WRC): GRAY DURAFLEX, BLACK AND WHITE AVAILABLE; INTERIOR WOOD SEALER
EXTREME WEATHER RESISTANT VERSION (WRX): GRAY FIBERGLASS COATING, BLACK AND WHITE AVAILABLE; INTERIOR GELCOAT SEALER
- SUSPENSION POINTS: 16 TOTAL, 4 EA TOP & 4 EA BOTTOM, 4 EA LEFT SIDE, 4 EA RIGHT SIDE. M10 THREADED PATTERN
- WEIGHT: 115.7 Kg (255 LBS)
- Ⓢ CENTER OF GRAVITY (CG) LOCATION AS INDICATED ON DRAWING
- ALL DIMENSIONS ARE FOR STANDARD VERSION ENCLOSURE, FOR WEATHER RESISTANT VERSIONS (WRC, WRX) ADD 0.060" (1.5MM) ADDITIONAL COATING THICKNESS
- STAINLESS STEEL HARDWARE ON WEATHER RESISTANT VERSIONS (WRC, WRX)

TOLERANCES
(UNLESS OTHERWISE SPECIFIED)

- X.XX ± .063 INCH
- X.X ± .125 INCH
- ANGULAR TOLERANCE OF 0°±30'
- FRACTIONAL DIMENSIONS ± 1/32
- * DIMENSIONS ARE INCHES
- * ALL DIMENSIONS ARE FINISHED DIMENSIONS
- * DO NOT SCALE DRAWING



JBL PROFESSIONAL
A Harman International Company
Northridge, California 91329 U.S.A.

TITLE
GEN,MRKT,DWG,VLA601Hi

SIZE **A** DRAWING NO. **1000333883** REV **E**

SCALE NTS SHEET 1 OF 1

NOTES: (UNLESS OTHERWISE SPECIFIED)