






THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JBL, INCORPORATED. THEY ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR MANUFACTURE OR APPARATUS WITHOUT WRITTEN PERMISSION.

ALL MATERIAL SPECIFIED ON THIS DRAWING SHALL COMPLY WITH EUROPEAN DIRECTIVE 2002/95/EC. **REVISION**

REVISIONS				
CHG.	INTR.	DESCRIPTION	DEPT.	D.C.



- NOTES:
1. DRIVERS: LF - 265H-15", HF - 2408H-1" MOUNTED ON A PT-HXXHF WAVEGUIDE
  2. SUSPENSION: 12 X M10 STAINLESS FITTINGS
  3. FINISH: 0.060" THICK COARSE TEXTURE FIBERGLASS (NOT REFLECTED IN DIMENSIONS ABOVE)
  4. GRILLE: 20 GA STAINLESS STEEL VAPOR BARRIER
  5. INPUT: SEALED GLANDNOT WITH 20' 2 CONDUCTOR CAPTIVE CABLE
  6. COLOR: STD GRAY WHITE - WH AND BLACK - BL ARE AVAILABLE AT NO EXTRA COST

TOLERANCES  
(UNLESS OTHERWISE SPECIFIED)

X.X ± .063 INCH  
X.XX ± .125 INCH  
ANGULAR TOLERANCE OF 0±.30°  
FRACTIONAL DIMENSIONS ± 1/32  
• ALL DIMENSIONS ARE FINISHED DIMENSIONS  
• DO NOT SCALE DRAWING

JBL

JBL PROFESSIONAL  
A Harman International Company  
Northridge, California 91329 U.S.A.

CUSTOMER DRAWING: AM5215-XX-WRX

SCALE NTS

SHEET 1 OF 1