

	Networked Audio		Ethernet	DSP	Channels		Watts Per Channel*			Low-Z / High-Z**	AUX Port	2x2 GPIO	Front Panel Display
	None	BLU link			2	4	300W	600W	1,200W				
CDi 2 300	●		●	●	●		●			●	●	●	●
CDi 2 600	●		●	●	●			●		●	●	●	●
CDi 2 1200	●		●	●	●				●	●	●	●	●
CDi 4 300	●		●	●		●	●			●	●	●	●
CDi 4 600	●		●	●		●		●		●	●	●	●
CDi 4 1200	●		●	●		●			●	●	●	●	●
CDi 2 300BL		●	●	●	●		●			●	●	●	●
CDi 2 600BL		●	●	●	●			●		●	●	●	●
CDi 2 1200BL		●	●	●	●	●			●	●	●	●	●
CDi 4 300BL		●	●	●		●	●			●	●	●	●
CDi 4 600BL		●	●	●		●		●		●	●	●	●
CDi 4 1200BL		●	●	●		●			●	●	●	●	●

* Measured @ 4Ω; Continuous; All channels driven; 1KHz; Minimum guaranteed power; Max distortion 0.5%; Duration 0.5 seconds

** Low-Z / High-Z configurable per individual channel; 70V / 100V configurable per individual channel