

WD-S8026

High-Power Professional Cinema Surround Speaker



HIGHLIGHTS ■

Premium JBL Sound & Design

Professional JBL performance with high SPL capabilities and maximum coverage

Easy & Versatile Deployment

Easily accessible binding post connectors and mountable via JBL QuickMount™, Omnimount® or APC Multimount brackets

Complete Cinema Solution

Combine with the Crown WD-A series amplifiers, JBL CPi2000 processor and other WD-S Series speakers for a fully integrated HARMAN / WANDA cinema audio solution

The JBL WD-S8026 high-power professional cinema surround speaker, part of the JBL WD-S Series, offers fidelity and performance synonymous with the JBL name to offer a premium sound experience. The 10-inch, 2-way WD-S8026 is optimized for small- to medium-sized theaters, delivering high SPLs and a throw capability of 40 feet for maximum coverage, along with superior headroom for improved performance and long-term stability.

The WD-S8026 is designed for hassle-free deployment and operation, integrating seamlessly with the entire JBL WD-S Series, which includes three screen speakers and two subwoofers.

Combine WD-S Series speakers with the JBL CPi2000 cinema processor and Crown WD-A Series amplifiers to build a fully integrated cinema sound solution.

KEY MESSAGES ■

PREMIUM SOUND WITHOUT THE PREMIUM PRICE

With the WD-S Series, it's never been easier to step into the stunning sound of a JBL cinema system. The WD-S Series WD-S8026 surround speaker delivers up to 125 dB peak SPL, with 110° x 90° coverage, thanks to an innovative angled cabinet baffle design. Pair with JBL WD-S Series WD-S2040, WD-S3046 and WD-S3080 screen speakers and WD-S1065 and WD-S1160 subwoofers for seamless coverage.

ROCK-SOLID AND RELIABLE

Trust the JBL WD-S Series to provide peak performance throughout the life of your investment: Systems are designed for superior overall efficiency; transducer-protection circuitry ensures long-term stability.

PURPOSEFUL DESIGN

The WD-S8026 features a 20° down-angled baffle when mounted flat against a wall, for improved aesthetics and ideal directivity. With an impedance of 8 ohms, multiple surrounds can be wired to a single amplifier channel, reducing amplification cost—while the increased 110° x 90° coverage pattern means fewer surrounds are needed to achieve full coverage.

BUILD AN INTEGRATED SOUND SYSTEM

Complete your JBL cinema sound system with the JBL CPi2000 cinema processor, which provides audio enhancement including DSP, room EQ tuning, volume control and system fault detection. The CPi2000 features WD-S Series speaker presets for better sound and performance and easier deployment, and can send amplifier and speaker status to a central TMS (Theater Management System) control system.

IN THE BOX ■

WD-S8026 2-Way Surround Speaker

WD-S8026

High-Power Professional Cinema Surround Speaker



APPLICATIONS ■

CINEMA THEATERS

Small- to medium-sized (80-150-seat) cinema theaters

FEATURES ■

- 10-inch transducer, 2-way configuration
- 110° x 90° (horizontal x vertical) coverage
- Cabinet features 20° down-angled front baffle
- Mounting design features JBL QuickMount™, Omnimount® or APC Multimount brackets
- Input terminals located on enclosure top for quick access
- Binding-post connectors are consistent with other JBL cinema speakers and easy to wire
- 260W rated power
- 8-ohm impedance allows multiple surround speakers to be wired to a single amplifier channel
- 125 dB peak SPL
- Frequency range: 55 Hz–18 kHz (-10 dB)
- Throw capability of up to 40 ft (12 m)

TECHNICAL SPECIFICATIONS ■

SYSTEM TYPE:	2-way passive surround
FREQUENCY RANGE (-10 dB):	55 Hz–18 kHz
SYSTEM IMPEDANCE:	8Ω
SYSTEM POWER:	260W
SENSITIVITY (4 PI):	92 dB
MAX PEAK SPL (2 PI):	125 dB
SYSTEM DIRECTIVITY (H x V):	110° x 90°
TRANSDUCERS:	LF: 1 x 10" HF: 1 x 1"
COMPLIANCE:	CE
MATERIAL:	Cabinet: MDF Horn: Plastic Grill: Fabric
COLOR/FINISH:	Matte black, vinyl
CONNECTORS:	Binding post
WEIGHT:	8.5 kg (18.74 lb)
DIMENSIONS (D x W x H):	254 x 370 x 470 mm (10 x 14.57 x 18.5 in)

ORDER SPECIFICATIONS ■

BOX DIMS (L x W x H):	313 x 404 x 529 mm (12.32 x 15.91 x 20.83 in)
SHIPPING WEIGHT:	11.5 kg (25.35 lb)
COUNTRY OF ORIGIN:	CN
UPC CODE:	691991037924



HARMAN Professional 8500 Balboa Blvd. Northridge, CA 91329 USA



CINEMABOX 3/F, Block A, Building 2, Vintage Creative Park, Langyuan, No.6, Langjiayuan, Chaoyang District, Beijing, China

© 2021 HARMAN International Industries, Incorporated. All rights reserved.
Features, specifications and appearance are subject to change without notice.

www.jblpro.com

© 2021 CINEMABOX Incorporated. All rights reserved.
Features, specifications and appearance are subject to change without notice.

Issued: 7/2021